


NORLAKE WALK-IN 5' X 6', 6' X 6', 6' X 8' OR 8' X 6' REFRIGERATOR OR FREEZER WITH FACE THROUGH WALL TYPICAL ELEVATION DETAIL



MODELS KLB66 OR KLC66 SHOWN ABOVE

NOTE: KLB = REFRIGERATOR, KLF = FREEZER, D = DRAIN, E = EJECTOR, F = FILL, G = GROUND

MODEL #	A	B	C	D	E	F	G	INTERIOR CU. FT.	VOLTS/HZ/PH	MINIMUM CIRCUIT AMPS	TOTAL SYSTEM AMPS	MAXIMUM FUSE SIZE
KLB45-CX-SUB	121.9cm	152.4cm	66cm	59" (149.8cm)	26" (66cm)	44 1/2" (113.0cm)	14 7/8" (37.7cm)	77	115/60/1	14.2	11.7	20
KLB46-CX-SUB	121.9cm	182.9cm	66cm	66" (167.6cm)	26" (66cm)	44 1/2" (113.0cm)	14 7/8" (37.7cm)	105	115/60/1	14.2	11.7	20
KLB56-CX-SUB	152.4cm	182.9cm	66cm	66" (167.6cm)	26" (66cm)	44 1/2" (113.0cm)	14 7/8" (37.7cm)	137	115/60/1	14.2	11.7	20
KLB66-CX-SUB	182.9cm	182.9cm	66cm	66" (167.6cm)	26" (66cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	168	208-230/60/1	10.5	8.7	15
KLB68-CX-SUB	243.8cm	182.9cm	66cm	66" (167.6cm)	37" (94cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	231	208-230/60/1	11.9	10	15
KLB683-CX-SUB	182.9cm	243.8cm	66cm	66" (167.6cm)	37" (94cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	231	208-230/60/1	11.9	10	15
KLB7446-CX-SUB	121.9cm	182.9cm	66cm	78" (198.1cm)	26" (66cm)	44 1/2" (113.0cm)	14 7/8" (37.7cm)	123	115/60/1	14.2	11.7	20
KLB7466-CX-SUB	182.9cm	182.9cm	66cm	78" (198.1cm)	37" (94cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	196	208-230/60/1	11.9	10	15
KLB7468-CX-SUB	243.8cm	182.9cm	66cm	78" (198.1cm)	37" (94cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	270	208-230/60/1	11.9	10	15
KLB74683-CX-SUB	182.9cm	243.8cm	66cm	78" (198.1cm)	37" (94cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	270	208-230/60/1	11.9	10	15
KLB7746-CX-SUB	121.9cm	182.9cm	66cm	78" (198.1cm)	26" (66cm)	44 1/2" (113.0cm)	14 7/8" (37.7cm)	123	115/60/1	14.2	11.7	20
KLB7756-CX-SUB	152.4cm	182.9cm	66cm	78" (198.1cm)	26" (66cm)	44 1/2" (113.0cm)	14 7/8" (37.7cm)	137	115/60/1	14.2	11.7	20
KLB7766-CX-SUB	182.9cm	182.9cm	66cm	78" (198.1cm)	37" (94cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	196	208-230/60/1	10.5	8.7	15
KLB7768-CX-SUB *	182.9cm	182.9cm	66cm	78" (198.1cm)	37" (94cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	270	208-230/60/1	11.9	8.7	15
KLB77683-CX-SUB *	182.9cm	243.8cm	66cm	78" (198.1cm)	37" (94cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	270	208-230/60/1	11.9	8.7	15
KLF45-Cx	121.9cm	152.4cm	66cm	59" (149.8cm)	26" (66cm)	44 1/2" (113.0cm)	14 7/8" (37.7cm)	77	208-230/60/1	13.4 DEFROST	10.7	20
KLF46-Cx	121.9cm	182.9cm	66cm	66" (167.6cm)	39" (99.1cm)	44 1/2" (113.0cm)	14 7/8" (37.7cm)	105	208-230/60/1	13.4 DEFROST	10.7	20
KLF56-Cx	152.4cm	182.9cm	66cm	66" (167.6cm)	39" (99.1cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	137	208-230/60/1	13.4 DEFROST	8.2	15
KLF66-CX *	182.9cm	182.9cm	66cm	66" (167.6cm)	39" (99.1cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	168	208-230/60/1	13.4 DEFROST	8.2	15
KLF68-CX *	243.8cm	182.9cm	66cm	66" (167.6cm)	36 1/2" (92.7cm)	48 1/4" (122.6cm)	22 7/8" (58.1cm)	231	208-230/60/1	10.8 DEFROST	9.1	15
KLF683-CX	182.9cm	243.8cm	66cm	66" (167.6cm)	36 1/2" (92.7cm)	48 1/4" (122.6cm)	22 7/8" (58.1cm)	231	208-230/60/1	10.8 DEFROST	9.1	15
KLF7746-CX *	121.9cm	182.9cm	66cm	78" (198.1cm)	34 7/8" (88.4cm)	48 1/4" (122.6cm)	22 7/8" (58.1cm)	123	208-230/60/1	13.4 DEFROST	8.2	15
KLF7756-Cx	152.4cm	182.9cm	66cm	78" (198.1cm)	36 1/2" (92.7cm)	48 1/4" (122.6cm)	22 7/8" (58.1cm)	137	208-230/60/1	10.8 DEFROST	9.1	15
KLF7766-Cx	182.9cm	182.9cm	66cm	78" (198.1cm)	39" (99.1cm)	48 1/4" (122.6cm)	22 7/8" (58.1cm)	196	208-230/60/1	13.4 DEFROST	8.2	15
KLF7768-CX	243.8cm	182.9cm	66cm	78" (198.1cm)	36 1/2" (92.7cm)	48 1/4" (122.6cm)	22 7/8" (58.1cm)	270	208-230/60/1	10.8 DEFROST	9.1	15
KLF77683-CX	182.9cm	243.8cm	66cm	78" (198.1cm)	36 1/2" (92.7cm)	48 1/4" (122.6cm)	22 7/8" (58.1cm)	270	208-230/60/1	10.8 DEFROST	9.1	15
KLF7846-CX *	121.9cm	182.9cm	66cm	78" (198.1cm)	39" (99.1cm)	48 1/4" (122.6cm)	22 7/8" (58.1cm)	113	208-230/60/1	13.4 DEFROST	8.2	15
KLF7856-Cx	152.4cm	182.9cm	66cm	78" (198.1cm)	36 1/2" (92.7cm)	48 1/4" (122.6cm)	22 7/8" (58.1cm)	149	208-230/60/1	10.8 DEFROST	9.1	15
KLF7866-Cx	182.9cm	182.9cm	66cm	78" (198.1cm)	39" (99.1cm)	48 1/4" (122.6cm)	22 7/8" (58.1cm)	184	208-230/60/1	13.4 DEFROST	8.2	15
KLF7868-CX	243.8cm	182.9cm	66cm	78" (198.1cm)	36 1/2" (92.7cm)	48 1/4" (122.6cm)	22 7/8" (58.1cm)	256	208-230/60/1	10.8 DEFROST	9.1	15
KLF78683-CX	182.9cm	243.8cm	66cm	78" (198.1cm)	36 1/2" (92.7cm)	48 1/4" (122.6cm)	22 7/8" (58.1cm)	256	208-230/60/1	10.8 DEFROST	9.1	15

MODEL: CA33-RR12
ALUMINUM WELDED CONSTRUCTION
HOLDS 12 FULL SIZE PANS (18" x 26")
OR 24 HALF SIZE PANS (13" x 18")
NSF APPROVED


LOCKWOOD DECK RETARDER

MODEL: CA27-RR12
ALUMINUM WELDED CONSTRUCTION
HOLDS 12 FULL SIZE PANS (18" x 26")
OR 24 HALF SIZE PANS (13" x 18")
NSF APPROVED


LOCKWOOD REACH-IN RETARDER

NOTE: EACH DOOR SECTION REQUIRES SEPARATE 115/60/1 HOOK UP AND DRAINS 2.3 AMPS. THESE SYSTEMS HAVE FAN MOTORS THAT REQUIRE SEPARATE 115/60/1 HOOK UP AND DRAIN .75 AMPS. ABOVE SPECIFICATIONS FOR CEILING MOUNT SYSTEMS AND INDOOR USE ONLY. WALL MOUNT AND REMOTE COMPRESSORS AVAILABLE. SEE MANUFACTURER FOR DETAILS. ALL TO BE DIRECT WIRE. NSF APPROVED. U.L. LISTING #E-486142 (REPORT #48). E.T.L. APPROVED. CSA FILE 18542-24.

NORLAKE KOLD LOCKER SERIES REFRIGERATOR AND FREEZER




NORLAKE WALK-IN 4' X 5' OR 4' X 6' REFRIGERATOR OR FREEZER WITH FACE THROUGH WALL TYPICAL ELEVATION DETAIL




MODELS KLB683 AND KLF683 (STD, 77 & 78) SHOWN ABOVE

THIS DRAWING APPLIES TO MODELS KLB AND KLF 45, 66, 68, 68 AND 683 IN STD, 74, 77 AND 78 SERIES. REFER TO NORLAKE KOLD LOCKER SERIES REFRIGERATOR AND FREEZER DRAWINGS AND TABLE BELOW FOR EXACT DIMENSIONS OF UNITS.


NORLAKE REFRIGERATOR / FREEZER




DUKE MANUFACTURING STAINLESS STEEL SINK




LOCKWOOD DECK RETARDER



LOCKWOOD REACH-IN RETARDER




LOCKWOOD RETARDER CABINET



INTERMETRO SHELVING SYSTEMS

NOTE: THESE DRAWINGS REPRESENT TYPICAL EQUIPMENT PURCHASED THROUGH DOCTOR'S ASSOCIATES INC. AND DOES NOT REPRESENT ANY EQUIPMENT PURCHASED LOCALLY BY THE FRANCHISEE/OWNER. OWNERS OF STORES OUTSIDE THE UNITED STATES AND CANADA MAY NEED ALTERNATE ELECTRICAL REQUIREMENTS. CONTACT YOUR DAI COORDINATOR OR THE MANUFACTURER FOR THE MODIFIED ELECTRICAL SPECIFICATIONS.


DUKE STAINLESS STEEL WORKTABLE



ICE-O-MATIC ICE CUBER

ICE0520 CUBER ON B42 STORAGE BIN (374 LBS. STORAGE CAPACITY) AIR-COOLED OR WATER-COOLED. ELECTRICAL SPECIFICATIONS: DIRECT WIRE PER CODE (3 WIRES) AIR-COOLED: 115V/60HZ/1PH 18.3 AMPS (20 MAX FUSE) 8441 BTUH. WATER-COOLED: 115V/60HZ/1PH 13.5 AMPS (15 MAX FUSE) 8356 BTUH. PLUMBING SPECIFICATIONS: 3/8\"/>


ICE-O-MATIC ICE CUBER



MANITOWOC ICE CUBER

Q-420 CUBER ON S-420 BIN TYPE: AIR-COOLED, WATER-COOLED REMOTE. ELECTRICAL SPECIFICATIONS: 115/60/1 20 AMP FUSE MIN. AIR-COOLED = 12.3 AMPS, WATER-COOLED = 11.4 AMPS WIRE DIRECT OR PER LOCAL CODE 220-240/50/1 ALSO AVAILABLE, SEE MANUFACTURER. PLUMBING SPECIFICATIONS: 3/8\"/>

MANITOWOC ICE CUBER



ZURN GREASE INTERCEPTOR


SIZE	INLET/OUTLET SIZE	FLOW RATE G.P.M. [L.P.M.]	WATER GAL. [L.]	GREASE LBS. [KG.]	APPROX. WT. LBS. [KG.]	C	C/E	F	G
100*	2	4 [15]	3 [11]	8 [4]	42 [19]	10 [254]	7 1/4 [184]	20 3/8 [518]	9 7/8 [251]
200*	2	7 [26]	5 [19]	14 [6]	53 [24]	11 1/4 [286]	8 1/8 [206]	21 3/4 [552]	11 7/8 [302]
300*	2	10 [38]	8 [23]	20 [9]	66 [30]	11 3/4 [298]	8 1/4 [210]	25 1/8 [638]	14 [356]
400*	2	15 [57]	10 [38]	30 [14]	83 [38]	13 3/8 [340]	8 3/8 [218]	27 1/8 [689]	16 3/4 [425]
500	2	20 [76]	16 [60]	40 [18]	99 [45]	15 [381]	11 3/4 [298]	30 [762]	17 1/4 [438]
600	3	25 [94]	21 [79]	50 [23]	124 [56]	17 [432]	12 1/2 [318]	32 1/4 [819]	19 7/8 [505]
700	3	35 [132]	30 [113]	70 [32]	151 [68]	18 3/4 [476]	14 1/4 [362]	34 1/8 [867]	22 1/2 [572]
800	3	50 [189]	40 [151]	100 [45]	180 [82]	21 1/2 [546]	16 [408]	36 [914]	24 1/2 [622]

*100, 200, 300 AND 400 ARE STANDARD SUBWAY MODEL SIZES.

ENGINEERING SPECIFICATIONS: ACID RESISTANT COATED INTERIOR AND EXTERIOR FABRICATED STEEL. INTERNAL AIR RELIEF BYPASS. BRONZE CLEANOUT PLUG. REMOVABLE PRESSURE EQUALIZING/FLOW DIFFUSING INLET BAFFLE. FIXED BOTTOM OUTLET BAFFLE. VISIBLE DOUBLE WALL TRAP SEAL.

ZURN GREASE INTERCEPTOR


NOTE: THESE DRAWINGS REPRESENT TYPICAL EQUIPMENT PURCHASED THROUGH DOCTOR'S ASSOCIATES INC. AND DOES NOT REPRESENT ANY EQUIPMENT PURCHASED LOCALLY BY THE FRANCHISEE/OWNER. OWNERS OF STORES OUTSIDE THE UNITED STATES AND CANADA MAY NEED ALTERNATE ELECTRICAL REQUIREMENTS. CONTACT YOUR DAI COORDINATOR OR THE MANUFACTURER FOR THE MODIFIED ELECTRICAL SPECIFICATIONS.



ICE-O-MATIC ICE CUBER

ICE0400 CUBER (AIR-COOLED OR WATER-COOLED) ICE0500 CUBER (AIR-COOLED, WATER-COOLED OR REMOTE CONDENSER) ICE0606 CUBER (AIR-COOLED, WATER-COOLED OR REMOTE CONDENSER) ON B55 STORAGE BIN (556 LBS. STORAGE CAPACITY) ELECTRICAL SPECIFICATIONS: DIRECT WIRE PER CODE (3 WIRES) ICE0400: (AIR-COOLED) 115V/60HZ/1PH 14.4 AMPS (15 MAX FUSE) 8064 BTUH. ICE0500: (AIR-COOLED) 115V/60HZ/1PH 13.4 AMPS (20 MAX FUSE) 8398 BTUH. (WATER-COOLED) 115V/60HZ/1PH 13.7 AMPS (20 MAX FUSE) 10843 BTUH. (REMOTE) 115V/60HZ/1PH 18.7 AMPS (20 MAX FUSE) 10881 BTUH. ICE0606: (AIR-COOLED) 208-230V/60HZ/1PH 12 AMPS (15 MAX FUSE) 11538 BTUH. (WATER-COOLED) 208-230V/60HZ/1PH 9.5 AMPS (15 MAX FUSE) 11473 BTUH. (REMOTE) 208-230V/60HZ/1PH 13 AMPS (15 MAX FUSE) 12269 BTUH. PLUMBING SPECIFICATIONS: 3/8\"/>


ICE-O-MATIC ICE CUBER



MANITOWOC ICE CUBER

Q-450 CUBER ON S-400 BIN TYPE: AIR-COOLED, WATER-COOLED, REMOTE. ELECTRICAL SPECIFICATIONS: 115/60/1 20 AMP FUSE MIN. AIR-COOLED = 12.8 AMPS, WATER-COOLED = 11.9 AMPS REMOTE = 9.6 AMPS WIRE DIRECT OR PER LOCAL CODE 220-240/50/1 ALSO AVAILABLE, SEE MANUFACTURER. PLUMBING SPECIFICATIONS: 3/8\"/>

MANITOWOC ICE CUBER



ZURN GREASE INTERCEPTOR

SIZE	INLET/OUTLET SIZE	FLOW RATE G.P.M. [L.P.M.]	WATER GAL. [L.]	GREASE LBS. [KG.]	APPROX. WT. LBS. [KG.]	C	C/E	F	G
100*	2	4 [15]	3 [11]	8 [4]	42 [19]	10 [254]	7 1/4 [184]	20 3/8 [518]	9 7/8 [251]
200*	2	7 [26]	5 [19]	14 [6]	53 [24]	11 1/4 [286]	8 1/8 [206]	21 3/4 [552]	11 7/8 [302]
300*	2	10 [38]	8 [23]	20 [9]	66 [30]	11 3/4 [298]	8 1/4 [210]	25 1/8 [638]	14 [356]
400*	2	15 [57]	10 [38]	30 [14]	83 [38]	13 3/8 [340]	8 3/8 [218]	27 1/8 [689]	16 3/4 [425]
500	2	20 [76]	16 [60]	40 [18]	99 [45]	15 [381]	11 3/4 [298]	30 [762]	17 1/4 [438]
600	3	25 [94]	21 [79]	50 [23]	124 [56]	17 [432]	12 1/2 [318]	32 1/4 [819]	19 7/8 [505]
700	3	35 [132]	30 [113]	70 [32]	151 [68]	18 3/4 [476]	14 1/4 [362]	34 1/8 [867]	22 1/2 [572]
800	3	50 [189]	40 [151]	100 [45]	180 [82]	21 1/2 [546]	16 [408]	36 [914]	24 1/2 [622]

*100, 200, 300 AND 400 ARE STANDARD SUBWAY MODEL SIZES.

ENGINEERING SPECIFICATIONS: ACID RESISTANT COATED INTERIOR AND EXTERIOR FABRICATED STEEL. INTERNAL AIR RELIEF BYPASS. BRONZE CLEANOUT PLUG. REMOVABLE PRESSURE EQUALIZING/FLOW DIFFUSING INLET BAFFLE. FIXED BOTTOM OUTLET BAFFLE. VISIBLE DOUBLE WALL TRAP SEAL.

ZURN GREASE INTERCEPTOR

NOTE: THESE DRAWINGS REPRESENT TYPICAL EQUIPMENT PURCHASED THROUGH DOCTOR'S ASSOCIATES INC. AND DOES NOT REPRESENT ANY EQUIPMENT PURCHASED LOCALLY BY THE FRANCHISEE/OWNER. OWNERS OF STORES OUTSIDE THE UNITED STATES AND CANADA MAY NEED ALTERNATE ELECTRICAL REQUIREMENTS. CONTACT YOUR DAI COORDINATOR OR THE MANUFACTURER FOR THE MODIFIED ELECTRICAL SPECIFICATIONS.

STORE MUST BE CONSTRUCTED AS DESIGNED IN THESE FLOOR PLANS SUBJECT TO FEDERAL, STATE AND LOCAL LAWS. RECIPIENT IS RESPONSIBLE FOR ENSURING COMPLIANCE WITH ALL LAWS. IF MODIFICATIONS ARE NECESSARY, PLEASE CONTACT THE FWH STORE DESIGN DEPARTMENT FOR WRITTEN APPROVAL OF THE REQUIRED CHANGES.

THIS DRAWING IS FURNISHED BY FWH ON BEHALF OF DOCTORS ASSOCIATES INC. (DAI) DB/IA. SUBWAY RECIPIENT MUST DETERMINE IF THIS DRAWING MUST BE SUBMITTED TO A LICENSED ARCHITECT OR SIMILAR PROFESSIONAL UNDER FEDERAL, STATE OR LOCAL LAW. ANY CHANGES MUST BE APPROVED BY DAI.

DO NOT SCALE DRAWING. WRITTEN DIMENSIONS TAKE PRECEDENCE OVER SCALED DIMENSIONS. INSPECTIONS AND MEASUREMENTS, FWH AND DAI SHALL NOT BE HELD RESPONSIBLE FOR THE GENERAL CONTRACTOR AND/OR FRANCHISEE/OWNER. ANY DISCREPANCY IN DIMENSIONS SHALL BE BROUGHT TO THE IMMEDIATE ATTENTION OF DAI'S AREA REPRESENTATIVE.

THE GENERAL CONTRACTOR AND EACH SUB-CONTRACTOR SHALL MAKE HIS OWN INSPECTIONS AND MEASUREMENTS, FWH AND DAI SHALL NOT BE HELD RESPONSIBLE FOR THE ACCURACY OF DIMENSIONS AND FOR ERRORS AND OMISSIONS IN THE DRAWINGS IF WRITTEN CONFIRMATION HAS NOT BEEN RECEIVED BY THE FWH STORE DESIGN DEPARTMENT.

THIS DRAWING AND THE INFORMATIONAL CONTENT HEREON IS THE CONFIDENTIAL PROPERTY OF DAI AND IS PROVIDED SOLELY FOR THE USE OF AUTHORIZED FRANCHISEES, THEIR AGENTS AND CONTRACTORS. RECIPIENT AGREES NOT TO REPRODUCE, COPY, USE OR TRANSMIT THIS DRAWING AND/OR ITS INFORMATIONAL CONTENT, IN WHOLE OR IN PART, OR TO ALLOW SUCH ACTION BY OTHERS FOR ANY PURPOSE, EXCEPT WITH THE WRITTEN PERMISSION OF DAI OR FWH ACTING ON BEHALF OF DAI. RECIPIENT FURTHER AGREES TO SURRENDER THIS DRAWING AND ANY DEMANDS HEREOF UPON DEMAND.

WORLD HEADQUARTERS
325 BIC DRIVE
MILFORD, CT 06461

(203) 877-4261
(800) 888-4848

TUSCANY II DECOR BACK-UP SHEET

REVISION:	BY:	DATE:
UPDATED ELECTRICAL SPECS ON REACH-INS	PMR	6/10/09

DATE: 10-31-08
DESIGNED BY: PATRICK ROSE
DRAWN BY: PMR
REVIEWED BY: PMR
SCALE: NOT TO SCALE