



**1 ROOF PLAN**  
A1.1 SCALE: 1/8" = 1'-0"

- ROOF PLAN GENERAL NOTES:**
- 1) SEE CRITERIA SHEET 01.0 A.B. 01.1 NOTES 8.4 AND 7.11 FOR SHELL INSULATION REQUIREMENTS.
  - 2) SEE CRITERIA SHEET 01.1 NOTE 2.5 FOR RAIN WATER LEADER REQUIREMENTS.
  - 3) WALK PAD PATH TO UNITS AND ACCESS DOORS REQUIRED.
  - 4) CONDENSATION DRAINS TO BE PIPED TO THE NEAREST ROOF DRAIN.
  - 5) ROOF REPORT REQUIRED SEE SHEET 01.0 NOTE 3.8, ROOF INSPECTION REPORT.
  - 6) ROOF DRAWS AND LOCATIONS SHOWN FOR CONCEPT ONLY. ACTUAL LOCATIONS MUST BE COORDINATED IN ADVANCE WITH AND APPROVED BY ROOF STORE DESIGNER. DIRECT CONNECTION TO STORM DRAIN SYSTEM IS REQUIRED OVER FLOOR TO DRAINAGE AT CURB OR DRIVE. DRAIN PIPES MUST NOT INTERFERE WITH INTERIOR STORE PLAN OR OPERATIONS.
  - 7) RTU'S SIZES AND LOCATIONS ARE SHOWN FOR CONCEPT ONLY. SEE SHEET 01.0 FOR ADDITIONAL INFORMATION.
  - 8) SKYLIGHTS - SUNSHOTS DOUBLE GLAZED SIGATURE SERIES DOME MODEL 82010-0000 WITH INTERIOR ALUMINUM FRAME. INTEGRAL CONDENSATION AND HEATPAE OUTLETS WHICH DRAIN INTERIOR MOISTURE TO OUTSIDE. INSTALLED PER MANUFACTURER'S RECOMMENDATIONS WITH BURGLAR BARS (2/A1.1).

