


1 PARTIAL ENLARGED PLAN
A4.0 SCALE: 1/4" = 1'-0"



UNLESS OTHERWISE NOTED ALL TOILET ROOM ACCESSORIES ARE BY BOBRICK. GENERAL CONTRACTOR SHALL PROVIDE AND INSTALL ALL TOILET ACCESSORIES AS NOTED.

A	SURFACE MOUNTED TOILET SEAT COVER DISPENSER 40" MAX. A.F.F. TO HIGHEST OPERABLE PART	B-721
B	SURFACE MOUNTED SOAP DISPENSER 40" MAX. A.F.F. TO HIGHEST OPERABLE PART	PROVIDED AND INSTALLED BY D.O.'S
C	SURFACE MOUNTED TOILET TISSUE DISPENSER 12" MAX. FROM FRONT EDGE OF TOILET SEAT AND 16" MIN. A.F.F. TO CENTERLINE OF DISPENSER	B-7892 JIMBO
D	SURFACE MOUNTED SANITARY WAPRON DISPOSAL 40" MAX. A.F.F. TO HIGHEST OPERABLE PART	B-770
E	5" S.S. GRAB BARS WITH CONCEALED MOUNTING LOCATED 33" TO CENTER LINE. BOTH BARS TO BE MOUNTED 12" FROM CORNER OF TOILET SEAT AND TO BE 45" MIN. LONG WITH THE FRONT END TO EXTEND 24" BEYOND FRONT EDGE OF TOILET SEAT, EACH BAR TO BE 36" MIN. LONG.	B-6808 W/ 2562 ANCHOR PLATES
F	MIRROR W/ S.S. FRAME, 18"x36" BOTTOM EDGE OF MIRROR 40" MAX. A.F.F.	B-165-1536
G	HAND DRYER, SEMI-RECESSED, GRAY COLOR 40" MIN. A.F.F. TO HIGHEST OPERABLE PART, 4" MAX. PROJECTION	B-7507
H	THE LAST DISPENSER (SOURCE: RETAIL RESOURCES, SUSAN HAYES, (212) 307-7193) MOUNTED 5" T-5" A.F.F.	M50260
I	TOILET ROOM PARTITIONS ACCESSIBLE STALL DOOR TO BE EQUIPPED WITH AUTOMATIC-CLOSING DEVICE, A CLEAR OPENING WIDTH OF 34" WITH THE DOOR POSITIVELY CLOSED. ITS GLASS PANEL TO BE 36" MIN. HIGH AND 24" MIN. WIDE. THE DOOR IS TO BE EQUIPPED WITH A LOOP OR U-SHAPED HANDLE IMMEDIATELY BELOW THE LATCH. THE LATCH MECHANISM SHALL NOT REQUIRE THE USER TO GRASP OR TWIST IN ORDER TO OPERATE	80BRN. DURABLE SERIES 100.67 OVERHEAD- EQUARED, INSTITUTIONAL HARDWARE COLOR-P-5 "BLU"X"K STAFF
J	DIAPER CHANGING STATION (SOURCE: KOALA (325) 829-2942) WHEN OPEN TOP OF TABLE TO BE 34" MAX. A.F.F.	181010-00

THE TOILET ROOM PLAN ON THIS SHEET IS SHOWN FOR CONCEPT AND MAY NOT MATCH THE SITE SPECIFIC PLAN. IF THAT IS THE CASE, THE DRAWINGS ON THIS SHEET ARE TO BE USED AS A GUIDE TO OUR PROTOTYPICAL REQUIREMENTS WHEN PREPARING THE SITE SPECIFIC TOILET ROOM PLANS, ELEVATIONS AND DETAILS.

- 4 ACCESSIBLE WATER SEPT: KHLER HIGHEST TOILET K-4302 (1.6 GPF) WITH K-4670-C SEAT AND SLOAN ROYAL 110 EXPOSED VAPOR WATER (3.5 GPF) WITH VACUUM BREAKER AND STOP. ARCHITECT OF RECORD TO COORDINATE COMPLIANCE WITH ALL LOCAL WATER CONSERVATION REQUIREMENTS AND PROPOSE SUBSTITUTIONS IF REQUIRED. -- HEIGHT TO BE 18 1/2" MEASURED TO THE TOP OF THE TOILET SEAT, CONTROLS TO BE NO MORE THAN 44" ABOVE THE FLOOR WITH A MAXIMUM 5-POUND-FORCE RECD FOR ACTIVATION.
- 16 WATER CLOSET: KHLER WELCHME K-1350 (1.6 GPF) WITH K-4670-C SEAT AND SLOAN ROYAL 110 EXPOSED VAPOR WATER (3.5 GPF) WITH VACUUM BREAKER AND STOP. ARCHITECT OF RECORD TO COORDINATE COMPLIANCE WITH ALL LOCAL WATER CONSERVATION REQUIREMENTS AND PROPOSE SUBSTITUTIONS IF REQUIRED.
- 2 RESTROOM LAVATORY: AMERICAN STANDARD, UNGLOSS 0355.012 WHITE, WITH HERITAGE CENTER FAUCET 5402.12V2V000 WITH VHSIT HANDLES -- FAUCET CONTROLS SHALL BE OPERABLE WITH ONE HAND. FAUCET SHALL NOT REQUIRE HOT CLOSING, PHISHING OR TYPING OF THE VHSIT WITH A MAXIMUM 5-POUND-FORCE RECD FOR ACTIVATION. ALL LAVATORIES TO BE MOUNTED WITH THE RIM 30" MIN. HIGHER THAN THE FLOOR FINISH. FAUCET SHALL BE 48" MIN. HIGHER THAN THE FLOOR FINISH. IN DEPTH, HOT WATER AND DRAIN PIPES UNDER ALL LAVATORIES SHALL BE INSULATED OR OTHERWISE COVERED, THERE SHALL BE NO SHAPP OR ABRASIVE SURFACES UNDER LAVATORIES.
- 3 URINAL: AMERICAN STANDARD, ALLSBRO 6541.1332 -- F81 TO PROJECT 14" HIGHER THAN 10" MAX. FROM WALL AND 17" MAX. AFFAIR.
- 4 (SEE 13.24.1) FOR LOCATION) JAWITER CLOSET SERVICE SINKS FLOSTORED 1000, 38" 24" 1" WITH STAINLESS STEEL CUP, FAUCET: CENTRAL BRASS #3054-0150-C SERVICE SINK 38" 24" 1"
- 5 DRINKING POINT: HALSEY-TAYLOR BARRIER-FREE NACF500-4A STAINLESS STEEL ELECTRIC WATER COOLER TUN, NO SUBSTITUTION -- INSTALLED WITH GROUND AT 34" (LOW) AND 41" (HIGH).
- 6 (SEE 13.24.1) FOR LOCATION) ELECTRIC 4 KW 110 GALLON WATER HEATER, SEE 6/4.0 FOR WATER HEATER SCHED.
- 7 CLOSET / BREAK ROOM SINK -- ELAYT GR50250 STAINLESS STEEL SINK W/ UNDERSEAL AMERICAN STANDARD, HERITAGE 7402.12V2V000 FAUCET W/ VHSIT BLADE HANDLES. FAUCET CONTROLS SHALL BE OPERABLE WITH ONE HAND. FAUCET SHALL NOT REQUIRE HOT CLOSING, PHISHING OR TYPING OF THE VHSIT WITH A MAXIMUM 5-POUND-FORCE RECD FOR ACTIVATION. SINK TO BE MOUNTED WITH THE COUNTER TOP 34" MAX AFFAIR, USE CLEAR-GLASS BLOW THE COUNTER SHALL EXTEND 30" MIN. W/ WIDTH AND 17" MIN. IN DEPTH, HOT WATER AND DRAIN PIPES UNDER THE COUNTER SHALL BE INSULATED OR OTHERWISE COVERED, THERE SHALL BE NO SHAPP OR ABRASIVE SURFACES UNDER COUNTERS.

5/8" A-C, G-1, EXT-APA PLYWOOD IN
 LIEU OF GWS INDICATED BY A 2"
 POLY-UREA @ RESTROOM AND JANITOR'S
 CLOSET WALLS ONLY (1 LAYER:
 A-WALL-FINISH-02)

FULL HEIGHT PARTITION WITH GWS BOTH SIDES

FULL HEIGHT ACOUSTICALLY INSULATED
AND SEALED FULL HEIGHT WALL

4' H X 8' X 3/4" PLYWOOD BACKBOARD
(LAYER: A-LL INSTALLED-PLYWOOD MOUNTING BOARD)

WC-1 "MONTCALM" WALLCOVERING (LAYER:
4-WALL-FINISH-VIC1) SEE 480

WALL BUMPER AT APPROX. 7" AND 31" A.F.F.
(LAYER A-WALL-FINISH-BUMPER). SEE 8/A4.0 AND
FINISH MATERIAL NOTE 14, SHEET A6.0, V.L

FLOORING TRANSITION, THRESHOLD, SADDLE, ETC.