

[illegible]

LEGENDS	
	EARTH
	ROCK FILL
	SAND/MORTAR/PLASTER
	CONCRETE CAST IN PLACE OR PRECAST
	BRICK
	CONCRETE BLOCK
	STONE INCLUDES MARBLE
	METAL OMIT INDICATION IN THIN MATERIAL
	METAL LATH
	WOOD, FINISH
	WOOD, FRAMING THROUGH MEMBER
	WOOD, FRAMING INTERRUPTED MEMBER
	PLYWOOD
	GYPSUM BOARD OMIT DOUBLE LINES AT SMALL SCALE
	ACOUSTIC TILE OR BOARD
	INSULATION, BATT
	INSULATION, RIGID
	DEMOUNTABLE PARTITION SEE DETAIL STUD SIZE WHEN NOT TYP.
	PERMANENT PARTITION WHERE OCCURS
	TYPICAL FURRING 2" UNLESS OTHERWISE NOTED
	GLAZED PARTITION
	WIRE MESH PARTITION
	CHAIN LINK FENCE
	1-HOUR RATED PARTITION

SCOPE OF WORK

1. DEMO EXISTING DEMISING WALLS
2. REMOVE FLOOR TILES AND WALL COVERINGS
3. EXISTING T-BAR CEILING TO REMAIN
4. EXISTING BATHROOM TO REMAIN
5. EXISTING HVAC TO REMAIN
6. EXISTING ELECTRICAL PANEL TO REMAIN
7. INSTALL NEW SUBWAY EQUIPMENT AS PER PLAN
8. INSTALL NEW SUBWAY FLOOR AND WALL TILE
9. INSTALL NEW TYPE II HOOD
10. INSTALL NEW VINYL WALL COVERINGS
11. GREASE TRAP TO BE INSTALLED PER CODE REQUIREMENT. SEE DETAIL 2

SHEET P-2

NUMBER OF EMPLOYEES PER SHIFT
4 EMPLOYEES PER SHIFT
WATER SERVICE DISTRICT
HELIX WATER DISTRICT
SEWER SERVICE DISTRICT
CITY OF LA MESA







LEGAL DESCRIPTION

CITY: LA MESA 1.23
AC M/L IN LOT 2 SEC 17-16-1W
CITY/MUNI/TWP: LA MESA

ASSESSOR'S PARCEL NUMBER
4902104600

NOTES:

1. TRASH ENCLOSURE INTERIOR WALL SURFACES ARE TO BE SMOOTH, SEALED, AND WASHABLE.
2. CONTRACTORS SHALL COMPLY WITH CONSTRUCTION AND DEMOLITION DEBRIS RECYCLING ORDINANCE PER SECTION 14.27 OF THE LA MESA MUNICIPAL CODE.
3. THIS PROJECT SHALL COMPLY WITH CITY OF LA MESA SECURITY ORDINANCE NO. 2145 PER SECTION 14.07 OF THE LA MESA MUNICIPAL CODE.
4. PROVIDE PANIC HARDWARE ON ALL EXIT DOORS.
5. PER TABLE A, GROUP A, 2007 CPC-1 UNISEX BATHROOM PROVIDED
6. 2008 NON-RESIDENTIAL EES INSTALLATION AND ACCEPTANCE FORMS TO BE ASSEMBLED AND POSTED WEATHER-PROTECTED WITHIN STRUCTURE.
7. APPLICABLE FORMS TO BE COMPLETED BY CONTRACTORS/INSTALLERS FOR REVIEW BY INSPECTORS PRIOR TO FINAL INSPECTION.
8. PROVIDE 2A-10BC FIRE EXTINGUISHER EVERY 75 FT. OF TRAVEL. MOUNTED ON WALLS 3-5 FT. ABOVE FINISHED FLOORS IN ACCESSIBLE AND VISIBLE LOCATIONS DETERMINED BY THE FIRE DEPARTMENT.
9. PROVIDE ADDRESS NUMBERS THAT ARE VISIBLE AND CONTRASTING IN COLOR TO BACKGROUND. SIZE OF NUMBERS AND MOUNTING LOCATION SHALL BE DETERMINED BY THE FIRE DEPARTMENT.

	<h1>SYMBOLS</h1>	<p>COLUMN LINE</p> <p>LETTERS IN VERT. DIRECTION NUMBERS IN HORIZ. DIRECTION</p>
	<p>DOOR SYMBOL</p> <p>SEE DOOR SCHEDULE</p>	
	<p>WINDOW TYPE</p> <p>SEE WINDOW SCHEDULE</p>	
	<p>LOUVER TYPE</p> <p>SKIP LETTERS "I" & "O"</p>	
	<p>REVISION</p> <p>CLOUD AROUND REVISION</p>	
	<p>MATCH LINE</p> <p>SHADED PORTION IS THE SIDE CONSIDERED</p>	

SHEET INDEX					
TS	TITLE SHEET (THIS SHEET)				
SITE	SITE PLAN				
1	FLOOR PLAN				
	P-1 PLUMBING NOTES				
1	FLOOR FINISH PLAN & CEILING PLAN				
	P-2 PLUMBING DETAILS				
1	SUBWAY EQUIPMENT DTLS				
	P-3 PLUMBING FLOOR PLAN				
2	SUBWAY EQUIPMENT DTLS				
	M-1 MECHANICAL NOTES				
3	SUBWAY EQUIPMENT DTLS				
	M-2 MECHANICAL FLOOR PLAN				
4	SUBWAY EQUIPMENT DTLS				
	E-1 ELECTRICAL NOTES				
	E-2 ELECTRICAL PLAN				
S-1	DETAILS				
S-2	STRUCTURAL FLOOR PLAN				
HC-1	HANDICAPPED DETAILS				
HC-2	HANDICAPPED DETAILS				
CN-1	NOTES				
EHS	HEALTH NOTES				
AREA ANALYSIS (TYPE V B)					
BASIC ALLOWABLE		ACTUAL SQUARE FOOTAGE		UNITY EQUATION	
B = 9000		1337 SQ. FT.		1337/9000 = 0.15<1.0	
EXITING ANALYSIS					
AREA	SQ. FTGE.	OCCUP. LOAD	FCTR	OCCUP. LOAD	REQ. NUM. OF EXITS
DINING AREA	638	1/15		43	45< 50 = 1 EXIT
STOCKROOM AREA	364	1/300		1.21	
FOOD PREP. AREA	161	1/200		.81	

GENERAL NOTES

- 1. GENERAL**

ALL WORK PERFORMED UNDER THIS CONTRACT SHALL CONFORM WITH THE APPLICABLE PORTIONS AND EDITIONS OF THE FOLLOWING CODES.

 - A. CALIFORNIA ADMINISTRATIVE CODE, TITLES 19, 20, 24
 - B. CALIFORNIA BUILDING CODE, 2007 EDITION
 - C. CALIFORNIA MECHANICAL CODE, 2007 EDITION
 - D. CALIFORNIA PLUMBING CODE, 2007 EDITION
 - E. CALIFORNIA ELECTRICAL CODE, LATEST EDITION
 - F. PUBLIC HEALTH CODE OF THE CALIFORNIA STATE DEPARTMENT OF PUBLIC HEALTH AND LOCAL HEALTH DEPARTMENT.
 - G. CALIFORNIA OCCUPATIONAL SAFETY AND HEALTH ACT, (CAL/OSHA), TITLE 8 "GENERAL SAFETY ORDERS".

H. RULES AND REGULATIONS OF THE STATE AND LOCAL FIRE MARSHALS.

J. A.D.A.A.G.

SPECIFICATIONS ARE A PART OF THIS CONTRACT AND SHALL TAKE PRECEDENCE OVER DRAWINGS.

DETAILS MARKED TYPICAL ON DRAWINGS ARE INTEND TO SHOW TYPICAL CONDITIONS FOR THE ENTIRE PROJECT AND ARE TO APPLY WHERE SIMILAR CONDITIONS OCCUR.

THE GENERAL CONTRACTOR SHALL BE RESPONSIBLE FOR VERIFICATION AND COORDINATION WITH OTHER CONTRACTORS TO ASSURE COMPLIANCE WITH DRAWINGS AND SPECIFICATIONS, AND THE ACCURATE LOCATION OF STRUCTURAL MEMBERS AND OPENINGS FOR MECHANICAL, ELECTRICAL, AND MISCELLANEOUS EQUIPMENT.
- 2. DIMENSIONS**

CHECK AND VERIFY ALL DIMENSIONS BEFORE COMMENCING WITH THIS PROJECT. REPORT ALL DISCREPANCIES TO THE ENGINEER BEFORE PROCEEDING.

DIMENSIONS SHOWN ON THE DRAWINGS ARE TO CENTER LINE OF STUDS, COLUMN OR GRID LINE OR TO FACE OF STUD PARTITIONS UNLESS OTHERWISE NOTED.

DO NOT SCALE DRAWINGS THE CONTRACTOR SHALL USE DIMENSIONS SHOWN ON THE DRAWINGS AND ACTUAL FIELD MEASUREMENTS. NOTIFY THE ENGINEER IF ANY DISCREPANCIES ARE FOUND.
- 3. DOORS**

UNLESS OTHERWISE NOTED DOORS SHALL BE LOCATED AS FOLLOWS:

 - A. WHERE DOOR FRAME IS NEXT TO ADJACENT WALL EDGE OF DOOR OPENING TO FACE OF WALL OR CABINET = 5".
 - B. IN CENTER OF WALL OF ROOM.
 - C. AS DIMENSIONED ON TYPICAL LAYOUT OF PARTICULAR ROOM.
- 5. CEILING**

CEILING HEIGHT SHALL BE 8'-0" IN OFFICE FROM FINISH FLOOR TO CEILING.

CEILING SUSPENSION SYSTEMS SHALL BE STABILIZED AGAINST LATERAL MOVEMENT IN ACCORDANCE WITH THE REQUIREMENTS OF THE CBC, 2007 EDITION
- 6. PARTITIONS**

TYPICAL PARTITION SHALL BE 2X4 STUDS WITH 1/2" GYPSUM BOARD ON EACH FACE TO A HEIGHT OF 8'-6". STUD SPACING SHALL BE 16" oc.
- 7. EXITS**

ALL EXIT DOORS SHALL BE OPENABLE FROM THE INSIDE WITHOUT USE OF KEY OR ANY SPECIAL KNOWLEDGE OR EFFORT.

[illegible]

<h2 style="text-align: center;">BUILDING DATA</h2>		
<h3>APPLICABLE CODES</h3>		
TITLE 19 PUBLIC SAFETY	CBC	UFC
TITLE 20 PUBLIC UTILITY	UPC	NEC
TITLE 24 BUILDING STANDARDS	UMC	ADAAG
CALIFORNIA MECHANICAL & PLUMBING CODES		
CITY OF SAN DIEGO REGULATIONS AND ORDINANCES		
2007 CALIFORNIA ELECTRICAL CODE		
2008 TITLE 24 ENERGY EFFICIENCY STANDARDS		
<h3>BUILDING OCCUPANCY</h3>		
B- PER 2007 CBC 303.1 EXCEPTION 1		
OCCUPANT LOAD LESS THAN 50 PERSONS		
SHALL BE CLASSIFIED AS GROUP B		
<h3>CONSTRUCTION TYPE</h3>		
VB SPRINKLERED		

<h2>OPERATION</h2> <h3>BY BUILDING PERMITS</h3> <p>INCLUDING THE DELIVERY, SETUP AND USE OF EQUIPMENT, SHALL BE FROM 6:00PM ON MONDAY THROUGH FRIDAY AND ON SATURDAYS. VIOLATIONS INCURRED ON SUNDAYS OR HOLIDAYS OBSERVED BY THE CITY OF SAN DIEGO SHALL BE CONSIDERED VIOLATIONS. VIOLATIONS REQUIRE A MANDATORY COURT COSTS UP TO \$2,701 PER OFFENSE. REPEAT VIOLATIONS WILL BE CONSIDERED A VIOLATION OF THE CITY OF SAN DIEGO ORDINANCES. THE CITY DETERMINES THAT APPROPRIATE MEASURES ARE IN COMPLIANCE WITH THE CITY OF SAN DIEGO ORDINANCES.</p>
--

ALL OPERATIONS AUTHORIZED BY BUILDING PERMITS, INCLUDING THE DELIVERY, SETUP AND USE OF EQUIPMENT, SHALL BE CONDUCTED ON PREMISES DURING THE HOURS OF 7:00AM TO 6:00PM ON MONDAY THROUGH FRIDAY AND ON SATURDAYS BETWEEN 8:00AM AND 5:00PM. NO WORK SHALL BE CONDUCTED ON SUNDAYS OR HOLIDAYS OBSERVED BY THE CITY OF SAN MARCOS. FAILURE TO COMPLY WILL RESULT IN THE ISSUANCE OF CITATIONS. CITATIONS REQUIRE A MANDATORY COURT APPEARANCE IN NORTH COUNTY SUPERIOR COURT AND COURT COSTS UP TO \$2,701 PER OFFENSE. REPEAT VIOLATIONS WILL RESULT IN SUSPENSION OF ALL WORK ON PREMISES UNTIL THE CITY DETERMINES THAT APPROPRIATE MEASURES ARE IN PLACE TO PREVENT ANY HOURS OF OPERATION VIOLATIONS.

P.E.
INCORPORATED
PASQUINI
ENGINEERING

903 H Street Suite 300
Bakersfield, Ca. 93304

Telephone: (661)-328-9600
Fax: (661)-328-9030

THESE PLANS ARE NOT
FOR CONSTRUCTION
UNLESS A "WET STAMP &
SIGNATURE" FROM BOTH
THE ENGINEER OF RECORD
AND A APPROVAL STAMP
WITH A "WET STAMP &
SIGNATURE" FROM THE
LOCAL GOVERNING
AGENCY ARE PRESENT.


DWG. BY	J.P.
CHK'D BY	
DATE	7/30/2010
JOB NO.	6190
FILE NO.	619022

EXP. 12/31/10

SHEET

TS

10/8/2010 SHEET



PROVIDE A SIGN INSIDE ABOVE MAIN ENTRY DOORS STATING "THIS DOOR TO REMAIN UNLOCKED WHEN BUILDING IS OCCUPIED". MINIMUM 1" HIGH LETTERS.

PROVIDE ILLUMINATED EXITS SIGNS PER CODE REQUIREMENTS

PRINTED: 10/8/2010 SHEET