

THIS DRAWING APPLIES TO MODELS KLB AND KLF 56, 66, 68 AND 683 IN STD, 74, 77 AND 78 SERIES. REFER TO NORLAKE KOLD LOCKER SERIES REFRIGERATOR AND FREEZER DRAWINGS AND TABLE BELOW FOR EXACT DIMENSIONS OF UNITS.

NORLAKE WALK-IN 5' X 6', 6' X 6', 6' X 8' OR 8' X 6' REFRIGERATOR OR FREEZER WITH FACE THROUGH WALL TYPICAL ELEVATION DETAIL



THIS DRAWING APPLIES TO MODELS KLB AND KLF 45 AND 46 IN 45, STD, 74, 77 AND 78 SERIES. REFER TO NORLAKE KOLD LOCKER SERIES REFRIGERATOR AND FREEZER DRAWINGS AND TABLE BELOW FOR EXACT DIMENSIONS OF UNITS.

NORLAKE WALK-IN 4' X 5' OR 4' X 6' REFRIGERATOR OR FREEZER WITH FACE THROUGH WALL TYPICAL ELEVATION DETAIL



MODEL KLF66 or KLC66 SHOWN ABOVE



MODEL KLF66 or KLC66 SHOWN ABOVE



MODELS KLB683 AND KLF683 (STD, 77 & 78) SHOWN ABOVE

NOTE: KLB = REFRIGERATOR. KLF = FREEZER.

MODEL #	A	B	C	D	E	F	G	INTERIOR CU. FT.	VOLTS/HZ/PH	MINIMUM CIRCUIT AMPS	TOTAL SYSTEM AMPS	MAXIMUM FUSE SIZE
KLB45–CX–SUB	4' (121.9cm)	5' (152.4cm)	26" (66cm)	59" (149.9cm)	26" (66cm)	44 1/2" (113cm)	14 7/8" (37.7cm)	77	115/60/1	14.2	11.7	20
KLB46–CX–SUB	4' (121.9cm)	6' (182.9cm)	26" (66cm)	66" (167.6cm)	26" (66cm)	44 1/2" (113cm)	14 7/8" (37.7cm)	105	115/60/1	14.2	11.7	20
KLB56–CX–SUB	5' (152.4cm)	6' (182.9cm)	26" (66cm)	66" (167.6cm)	26" (66cm)	44 1/2" (113cm)	14 7/8" (37.7cm)	137	115/60/1	14.2	11.7	20
KLB66–CX–SUB	6' (182.9cm)	6' (182.9cm)	26" (66cm)	66" (167.6cm)	37" (94cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	168	208–230/60/1	10.5	8.7	15
KLB68–CX–SUB	8' (243.8cm)	6' (182.9cm)	26" (66cm)	66" (167.6cm)	37" (94cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	231	208–230/60/1	11.9	10	15
KLB683–CX–SUB	6' (182.9cm)	8' (243.8cm)	26" (66cm)	66" (167.6cm)	37" (94cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	231	208–230/60/1	11.9	10	15
KLB7446–CX–SUB	4' (121.9cm)	6' (182.9cm)	26" (66cm)	78" (198.1cm)	26" (66cm)	44 1/2" (113cm)	14 7/8" (37.7cm)	123	115/60/1	14.2	11.7	20
KLB7466–CX–SUB	6' (182.9cm)	6' (182.9cm)	26" (66cm)	78" (198.1cm)	37" (94cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	196	208–230/60/1	11.9	10	15
KLB7468–CX–SUB	8' (243.8cm)	6' (182.9cm)	26" (66cm)	78" (198.1cm)	37" (94cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	270	208–230/60/1	11.9	10	15
KLB74683–CX–SUB	6' (182.9cm)	8' (243.8cm)	26" (66cm)	78" (198.1cm)	37" (94cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	270	208–230/60/1	11.9	10	15
KLB7746–CX–SUB	4' (121.9cm)	6' (182.9cm)	26" (66cm)	78" (198.1cm)	26" (66cm)	44 1/2" (113cm)	14 7/8" (37.7cm)	123	115/60/1	14.2	11.7	20
KLB7756–CX–SUB	5' (152.4cm)	6' (182.9cm)	26" (66cm)	78" (198.1cm)	26" (66cm)	44 1/2" (113cm)	14 7/8" (37.7cm)	137	115/60/1	14.2	11.7	20
KLB7766–CX–SUB	6' (182.9cm)	6' (182.9cm)	26" (66cm)	78" (198.1cm)	37" (94cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	196	208–230/60/1	10.5	8.7	15
KLB7768–CX–SUB *	8' (243.8cm)	6' (182.9cm)	26" (66cm)	78" (198.1cm)	37" (94cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	270	208–230/60/1	11.9	8.7	15
KLB77683–CX–SUB *	6' (182.9cm)	8' (243.8cm)	26" (66cm)	78" (198.1cm)	37" (94cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	270	208–230/60/1	11.9	8.7	15
KLF45–Cx	4' (121.9cm)	5' (152.4cm)	26" (66cm)	59" (149.9cm)	39" (99.1cm)	44 1/2" (113cm)	14 7/8" (37.7cm)	77	208–230/60/1	13.4 13.4 DEFROST	10.7	20
KLF46–Cx	4' (121.9cm)	6' (182.9cm)	26" (66cm)	66" (167.6cm)	39" (99.1cm)	44 1/2" (113cm)	14 7/8" (37.7cm)	105	208–230/60/1	13.4 13.4 DEFROST	10.7	20
KLF56–Cx	5' (152.4cm)	6' (182.9cm)	26" (66cm)	66" (167.6cm)	39" (99.1cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	137	208–230/60/1	13.4 13.4 DEFROST	8.2	15
KLF66–CX *	6' (182.9cm)	6' (182.9cm)	26" (66cm)	66" (167.6cm)	39" (99.1cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	168	208–230/60/1	13.4 13.4 DEFROST	8.2	15
KLF68–CX *	8' (243.8cm)	6' (182.9cm)	26" (66cm)	66" (167.6cm)	36 1/2" (92.7cm)	59" (149.9cm)	22 7/8" (58.1cm)	231	208–230/60/1	8.8 10.8 DEFROST	9.1	15
KLF683–CX	6' (182.9cm)	8' (243.8cm)	26" (66cm)	66" (167.6cm)	36 1/2" (92.7cm)	59" (149.9cm)	22 7/8" (58.1cm)	231	208–230/60/1	8.8 10.8 DEFROST	9.1	15
KLF7746–CX *	4' (121.9cm)	6' (182.9cm)	26" (66cm)	78" (198.1cm)	39" (99.1cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	123	208–230/60/1	13.4 13.4 DEFROST	8.2	15
KLF7756–Cx	5' (152.4cm)	6' (182.9cm)	26" (66cm)	78" (198.1cm)	36 1/2" (92.7cm)	59" (149.9cm)	22 7/8" (58.1cm)	137	208–230/60/1	8.8 10.8 DEFROST	9.1	15
KLF7766–CX	6' (182.9cm)	6' (182.9cm)	26" (66cm)	78" (198.1cm)	39" (99.1cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	196	208–230/60/1	13.4 13.4 DEFROST	8.2	15
KLF7768–CX	8' (243.8cm)	6' (182.9cm)	26" (66cm)	78" (198.1cm)	36 1/2" (92.7cm)	59" (149.9cm)	22 7/8" (58.1cm)	270	208–230/60/1	8.8 10.8 DEFROST	9.1	15
KLF77683–CX	6' (182.9cm)	8' (243.8cm)	26" (66cm)	78" (198.1cm)	36 1/2" (92.7cm)	59" (149.9cm)	22 7/8" (58.1cm)	270	208–230/60/1	8.8 10.8 DEFROST	9.1	15
KLF7846–CX *	4' (121.9cm)	6' (182.9cm)	26" (66cm)	78" (198.1cm)	39" (99.1cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	113	208–230/60/1	13.4 13.4 DEFROST	8.2	15
KLF7856–Cx	5' (152.4cm)	6' (182.9cm)	26" (66cm)	78" (198.1cm)	36 1/2" (92.7cm)	59" (149.9cm)	22 7/8" (58.1cm)	149	208–230/60/1	8.8 10.8 DEFROST	9.1	15
KLF7866–CX	6' (182.9cm)	6' (182.9cm)	26" (66cm)	78" (198.1cm)	39" (99.1cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	184	208–230/60/1	13.4 13.4 DEFROST	8.2	15
KLF7868–CX	8' (243.8cm)	6' (182.9cm)	26" (66cm)	78" (198.1cm)	36 1/2" (92.7cm)	59" (149.9cm)	22 7/8" (58.1cm)	256	208–230/60/1	8.8 10.8 DEFROST	9.1	15
KLF78683–CX	6' (182.9cm)	8' (243.8cm)	26" (66cm)	78" (198.1cm)	36 1/2" (92.7cm)	59" (149.9cm)	22 7/8" (58.1cm)	256	208–230/60/1	8.8 10.8 DEFROST	9.1	15

NOTE:
EACH DOOR SECTION REQUIRES SEPERATE 115/60/1 HOOK UP AND DRAWS 2.3 AMPS.
*THESE SYSTEMS HAVE FAN MOTORS THAT REQUIRE SEPERATE 115/60/1 HOOK UP AND DRAW .75 AMPS. ABOVE SPECIFICATIONS FOR CEILING MOUNT SYSTEMS AND INDOOR USE ONLY.
WALL MOUNT AND REMOTE COMPRESSORS AVAILABLE. SEE MANUFACTURER FOR DETAILS.
ALL TO BE DIRECT WIRED.
NSF APPROVED. UL LISTING #E–486142 (REPORT #48). E.T.L. APPROVED. CSA FILE 18542–24.

MANUFACTURER CLEARANCE SPECIFICATIONS:

DO NOT STORE BOXES ON THE TOP OF COOLER OR FREEZER. STORED OBJECTS WILL OBSTRUCT AIR FLOW AND CAUSE VENTILATION PROBLEMS FOR THE REFRIGERATION SYSTEMS.

24" CLEARANCE IS RECOMMENDED FROM TOP OF ROOF MOUNTED CAPSULE PAK REFRIGERATION SYSTEM TO CEILING FOR SERVICE PURPOSES (6" MINIMUM).

OPENING WITH GRILL OR LOUVERS (MIN. SIZE 15" H X 26" W) IN HEADER WALL RECOMMENDED FOR VENTILATION OF ROOF MOUNTED COMPRESSOR.

12" CLEARANCE IS RECOMMENDED ON BOTH SIDES OF THE WALL MOUNTED CAPSULE PAK FOR PROPER AIR FLOW

NORLAKE KOLD LOCKER SERIES REFRIGERATOR AND FREEZER



MODEL NR803SSS/O OR NF803SSS/O SHOWN

MODEL #	VOLTS/HZ/PH	AMPS.	INTERIOR CU. FT.
NR241SSS/O	115/60/1	8.6	22.5
NR522SSS/O	115/60/1	10.7	48.8
NR803SSS/O	115/60/1	10.4	75.0
NF241SSS/O	115/60/1	12	22.5
NF522SSS/O	115/60/1	12.4	48.8
*NF803SSS/O	115/60/1	15	75.0

*20 AMP FUSE IS REQUIRED.

ALL SYSTEMS – CORD & PLUG SUPPLIED NSF APPROVED UL LISTING #SA–3931 CSA LISTING 18542–23

NORLAKE REFRIGERATOR / FREEZER



THREE COMPARTMENT SINK WITH TWO 18" DRAINBOARDS SHOWN ABOVE.
AVAILABLE WITH ONE, TWO, THREE OR FOUR COMPARTMENTS AND ZERO, ONE OR TWO 18"[45.7cm], 24"[61cm] OR 30"[76.2cm] DRAINBOARDS.
THREE COMPARTMENT CORNER SINKS ALSO AVAILABLE.
1/2" NPT WATER LINES. 2" DRAINS.
UL AND C–UL LISTED.

DUKE MANUFACTURING STAINLESS STEEL SINK



MODEL: CA33–RR12
ALUMINUM WELDED CONSTRUCTION
HOLDS 12 FULL SIZE PANS (18" X 26") OR 24 HALF SIZE PANS (13" X 18")
NSF APPROVED

LOCKWOOD DECK RETARDER



MODEL: CA27–RR12
ALUMINUM WELDED CONSTRUCTION
HOLDS 12 FULL SIZE PANS (18" X 26") OR 24 HALF SIZE PANS (13" X 18")
NSF APPROVED

LOCKWOOD REACH-IN RETARDER



MODEL: CA60–RR25
HOLDS 25 HALF SIZE PANS (13" X 18")
MODEL: CA76–RR33
HOLDS 33 HALF SIZE PANS (13" X 18")
*CA76–RR33 TO BE USED WITH 77 SERIES REFRIGERATOR.
ALUMINUM WELDED CONSTRUCTION
NSF APPROVED

LOCKWOOD RETARDER CABINET



AVAILABLE SIZES ARE:
WIDTH: 14", 18", 21", 24"
(35.6, 45.7, 53.3, 61cm)
LENGTH: 24", 30", 36", 42", 48", 60" AND 72"
(61, 76.2, 91.4, 106.7, 121.9, 152.4, 182.9cm)
4 OR 5 TIER

INTERMETRO SHELVING SYSTEMS



WITH GALVANIZED UNDERSHELF
TABLES 96" AND LARGER HAVE SIX LEGS
DRAWERS ARE OPTIONAL
NSF APPROVED

DUKE STAINLESS STEEL WORKTABLE

NOTE:
THESE DRAWINGS REPRESENT TYPICAL EQUIPMENT PURCHASED THROUGH DOCTOR'S ASSOCIATES INC. AND DOES NOT REPRESENT ANY EQUIPMENT PURCHASED LOCALLY BY THE FRANCHISEE/OWNER. OWNERS OF STORES OUTSIDE THE UNITED STATES AND CANADA MAY NEED ALTERNATE ELECTRICAL REQUIREMENTS. CONTACT YOUR DAI COORDINATOR OR THE MANUFACTURER FOR THE MODIFIED ELECTRICAL SPECIFICATIONS.

STORE MUST BE CONSTRUCTED AS DESIGNED IN THESE FLOOR PLANS SUBJECT TO FEDERAL, STATE AND LOCAL LAWS. RECIPIENT IS RESPONSIBLE FOR ENSURING COMPLIANCE WITH ALL LAWS. IF MODIFICATIONS ARE NECESSARY, PLEASE CONTACT THE FWH STORE DESIGN DEPARTMENT FOR WRITTEN APPROVAL OF THE REQUIRED CHANGES.

THIS DRAWING IS FURNISHED BY FWH ON BEHALF OF DOCTORS ASSOCIATES INC. ("DAI") D/B/A SUBWAY. RECIPIENT MUST DETERMINE IF THIS DRAWING MUST BE SUBMITTED TO A LICENSED ARCHITECT OR SIMILAR PROFESSIONAL UNDER FEDERAL, STATE OR LOCAL LAW. ANY CHANGES MUST BE APPROVED BY DAI.

DO NOT SCALE DRAWING. WRITTEN DIMENSIONS TAKE PRECEDENCE OVER SCALED DIMENSIONS, AND SHALL BE VERIFIED IN THE FIELD BY THE GENERAL CONTRACTOR AND/OR FRANCHISEE/OWNER. ANY DISCREPANCY IN DIMENSIONS SHALL BE BROUGHT TO THE IMMEDIATE ATTENTION OF DAI'S AREA DEVELOPMENT AGENT OR DESIGNATED FIELD REPRESENTATIVE.

THE GENERAL CONTRACTOR AND EACH SUB-CONTRACTOR SHALL MAKE HIS OWN INSPECTIONS AND MEASUREMENTS. FWH AND DAI SHALL NOT BE HELD RESPONSIBLE FOR THE ACCURACY OF DIMENSIONS AND FOR ERRORS AND OMISSIONS IN THE DRAWINGS IF WRITTEN CONFIRMATION HAD NOT BEEN RECEIVED BY THE FWH STORE DESIGN DEPARTMENT.

THIS DRAWING AND THE INFORMATIONAL CONTENT HERE OF IS THE CONFIDENTIAL PROPERTY DAI OF AND IS PROVIDED SOLELY FOR THE USE OF AUTHORIZED FRANCHISEES, THEIR AGENTS AND CONTRACTORS. RECIPIENT AGREES NOT TO REPRODUCE, COPY, USE OR TRANSMIT THIS DRAWING AND/OR ITS INFORMATIONAL CONTENT, IN WHOLE OR IN PART, OR TO ALLOW SUCH ACTION BY OTHERS, FOR ANY PURPOSE, EXCEPT WITH THE WRITTEN PERMISSION OF DAI OR FWH ACTING ON BEHALF OF DAI. RECIPIENT FURTHER AGREES TO SURRENDER THIS DRAWING AND ANY PERMITTED COPIES HEREOF UPON DEMAND.

SUBWAY®
WORLD HEADQUARTERS
325 BIC DRIVE
MILFORD, CT 06461
(203) 877-4281
(800) 888-4848

TUSCANY II DECOR BACK-UP SHEET

REVISION:	BY	DATE
UPDATED ELECTRICAL SPECS ON REACH-INS	*PMR*	*6/1/09*

DATE: *10-31-08*
DESIGNED BY: *PATRICK ROSE*
DRAWN BY: *PMR*
REVIEWED BY: *PMR*
SCALE: NOT TO SCALE

SHEET #: *3 of 4*

PRINTED 11/17/2010

©2010 DOCTORS ASSOCIATES, INC.