


**NORLAKE WALK-IN 5' X 6', 6' X 6', 6' X 8' OR 8' X 6' REFRIGERATOR OR FREEZER WITH FACE THROUGH WALL TYPICAL ELEVATION DETAIL**



**NORLAKE WALK-IN 4' X 5' OR 4' X 6' REFRIGERATOR OR FREEZER WITH FACE THROUGH WALL TYPICAL ELEVATION DETAIL**

NOTE: KLB = REFRIGERATOR, KLF = FREEZER.

MODEL #	A	B	C	D	E	F	G	INTERIOR CU. FT.	VOLTS/HZ/PH	MINIMUM CIRCUIT AMPS	TOTAL SYSTEM AMPS	MAXIMUM FUSE SIZE
KLB45-CX-SUB	4' (121.9cm)	5' (152.4cm)	26" (66cm)	59" (149.9cm)	26" (66cm)	44 1/2" (113cm)	14 7/8" (37.7cm)	77	115/60/1	14.2	11.7	20
KLB46-CX-SUB	4' (121.9cm)	5' (152.4cm)	26" (66cm)	59" (149.9cm)	26" (66cm)	44 1/2" (113cm)	14 7/8" (37.7cm)	105	115/60/1	14.2	11.7	20
KL856-CX-SUB	5' (152.4cm)	182.9cm	26" (66cm)	66" (167.6cm)	26" (66cm)	44 1/2" (113cm)	14 7/8" (37.7cm)	137	115/60/1	14.2	11.7	20
KL866-CX-SUB	5' (152.4cm)	182.9cm	26" (66cm)	66" (167.6cm)	37" (94cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	168	208-230/60/1	10.5	8.7	15
KL868-CX-SUB	6' (182.9cm)	243.8cm	26" (66cm)	66" (167.6cm)	37" (94cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	231	208-230/60/1	11.9	10	15
KL8683-CX-SUB	6' (182.9cm)	243.8cm	26" (66cm)	66" (167.6cm)	37" (94cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	231	208-230/60/1	11.9	10	15
KL87446-CX-SUB	4' (121.9cm)	182.9cm	26" (66cm)	78" (198.1cm)	26" (66cm)	44 1/2" (113cm)	14 7/8" (37.7cm)	123	115/60/1	14.2	11.7	20
KL87466-CX-SUB	4' (121.9cm)	182.9cm	26" (66cm)	78" (198.1cm)	37" (94cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	196	208-230/60/1	11.9	10	15
KL87468-CX-SUB	4' (121.9cm)	182.9cm	26" (66cm)	78" (198.1cm)	37" (94cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	270	208-230/60/1	11.9	10	15
KL874683-CX-SUB	4' (121.9cm)	182.9cm	26" (66cm)	78" (198.1cm)	37" (94cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	270	208-230/60/1	11.9	10	15
KL87746-CX-SUB	4' (121.9cm)	182.9cm	26" (66cm)	78" (198.1cm)	37" (94cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	123	115/60/1	14.2	11.7	20
KL87756-CX-SUB	5' (152.4cm)	182.9cm	26" (66cm)	78" (198.1cm)	26" (66cm)	44 1/2" (113cm)	14 7/8" (37.7cm)	137	115/60/1	14.2	11.7	20
KL87766-CX-SUB	6' (182.9cm)	182.9cm	26" (66cm)	78" (198.1cm)	37" (94cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	196	208-230/60/1	10.5	8.7	15
KL87768-CX-SUB *	4' (121.9cm)	182.9cm	26" (66cm)	78" (198.1cm)	37" (94cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	270	208-230/60/1	11.9	8.7	15
KL877683-CX-SUB *	4' (121.9cm)	182.9cm	26" (66cm)	78" (198.1cm)	37" (94cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	270	208-230/60/1	11.9	8.7	15
KLF45-Cx	4' (121.9cm)	152.4cm	26" (66cm)	59" (149.9cm)	39" (99.1cm)	44 1/2" (113cm)	14 7/8" (37.7cm)	77	208-230/60/1	13.4 13.4 DEFROST	10.7	20
KLF46-Cx	4' (121.9cm)	182.9cm	26" (66cm)	66" (167.6cm)	39" (99.1cm)	44 1/2" (113cm)	14 7/8" (37.7cm)	105	208-230/60/1	13.4 13.4 DEFROST	10.7	20
KLF56-Cx	5' (152.4cm)	182.9cm	26" (66cm)	66" (167.6cm)	39" (99.1cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	137	208-230/60/1	13.4 13.4 DEFROST	8.2	15
KLF68-CX *	6' (182.9cm)	182.9cm	26" (66cm)	66" (167.6cm)	39" (99.1cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	168	208-230/60/1	13.4 13.4 DEFROST	8.2	15
KLF68-CX *	6' (182.9cm)	182.9cm	26" (66cm)	66" (167.6cm)	39" (99.1cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	231	208-230/60/1	10.8 DEFROST	9.1	15
KLF683-CX	6' (182.9cm)	243.8cm	26" (66cm)	66" (167.6cm)	36 1/2" (92.7cm)	59" (149.9cm)	22 7/8" (58.1cm)	231	208-230/60/1	10.8 DEFROST	9.1	15
KL87746-CX *	4' (121.9cm)	182.9cm	26" (66cm)	78" (198.1cm)	39" (99.1cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	123	208-230/60/1	13.4 13.4 DEFROST	8.2	15
KL87756-Cx	5' (152.4cm)	182.9cm	26" (66cm)	66" (167.6cm)	39" (99.1cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	137	208-230/60/1	13.4 13.4 DEFROST	9.1	15
KL87766-CX	6' (182.9cm)	182.9cm	26" (66cm)	78" (198.1cm)	39" (99.1cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	196	208-230/60/1	13.4 13.4 DEFROST	8.2	15
KL87768-CX	6' (182.9cm)	182.9cm	26" (66cm)	78" (198.1cm)	36 1/2" (92.7cm)	59" (149.9cm)	22 7/8" (58.1cm)	270	208-230/60/1	10.8 DEFROST	9.1	15
KL877683-CX	6' (182.9cm)	243.8cm	26" (66cm)	66" (167.6cm)	36 1/2" (92.7cm)	59" (149.9cm)	22 7/8" (58.1cm)	270	208-230/60/1	10.8 DEFROST	9.1	15
KLF7746-CX *	4' (121.9cm)	182.9cm	26" (66cm)	78" (198.1cm)	39" (99.1cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	113	208-230/60/1	13.4 13.4 DEFROST	8.2	15
KLF7856-Cx	5' (152.4cm)	182.9cm	26" (66cm)	66" (167.6cm)	36 1/2" (92.7cm)	59" (149.9cm)	22 7/8" (58.1cm)	149	208-230/60/1	10.8 DEFROST	9.1	15
KLF7866-CX	6' (182.9cm)	182.9cm	26" (66cm)	78" (198.1cm)	39" (99.1cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	184	208-230/60/1	13.4 13.4 DEFROST	8.2	15
KLF7868-CX	6' (182.9cm)	182.9cm	26" (66cm)	78" (198.1cm)	36 1/2" (92.7cm)	59" (149.9cm)	22 7/8" (58.1cm)	256	208-230/60/1	10.8 DEFROST	9.1	15
KLF78683-CX	6' (182.9cm)	243.8cm	26" (66cm)	66" (167.6cm)	36 1/2" (92.7cm)	59" (149.9cm)	22 7/8" (58.1cm)	256	208-230/60/1	10.8 DEFROST	9.1	15

MODEL: CA33-RR12

ALUMINUM WELDED CONSTRUCTION  
HOLDS 12 FULL SIZE PANS (18" x 26")  
OR 24 HALF SIZE PANS (13" x 18")  
NSF APPROVED

**LOCKWOOD DECK RETARDER**


MODEL: CA27-RR12

ALUMINUM WELDED CONSTRUCTION  
HOLDS 12 FULL SIZE PANS (18" x 26")  
OR 24 HALF SIZE PANS (13" x 18")  
NSF APPROVED

**LOCKWOOD REACH-IN RETARDER**

NOTE: EACH DOOR SECTION REQUIRES SEPARATE 115/60/1 HOOK UP AND DRAWS 2.3 AMPS. THESE SYSTEMS HAVE FAN MOTORS THAT REQUIRE SEPARATE 115/60/1 HOOK UP AND DRAW .75 AMPS. ABOVE SPECIFICATIONS FOR CEILING MOUNT SYSTEMS AND INDOOR USE ONLY. WALL, MOUNT AND REMOTE COMPRESSORS AVAILABLE. SEE MANUFACTURER FOR DETAILS. ALL TO BE DIRECT WIRE. NSF APPROVED. UL LISTING #E-486142 (REPORT #48). E.T.L. APPROVED. CSA FILE 18542-24.

**NORLAKE KOLD LOCKER SERIES REFRIGERATOR AND FREEZER**




MODEL NR803SSS/O OR NF803SSS/O SHOWN

MODEL #	VOLTS/HZ/PH	AMPS	INTERIOR CU. FT.
NR241SSS/O	115/60/1	8.6	22.5
NR522SSS/O	115/60/1	10.7	48.8
NR803SSS/O	115/60/1	10.4	75.0
NF241SSS/O	115/60/1	12	22.5
NF522SSS/O	115/60/1	12.4	48.8
NF803SSS/O	115/60/1	15	75.0


ALL SYSTEMS - CORD & PLUG SUPPLIED NSF APPROVED UL LISTING #SA-3931 CSA LISTING 18542-23

**NORLAKE REFRIGERATOR / FREEZER**




THREE COMPARTMENT SINK WITH TWO 18\"/>


**DUKE MANUFACTURING STAINLESS STEEL SINK**




**LOCKWOOD DECK RETARDER**




**LOCKWOOD REACH-IN RETARDER**



**LOCKWOOD RETARDER CABINET**




**INTERMETRO SHELVING SYSTEMS**




ICEO520 CUBER ON B42 STORAGE BIN (374 LBS. STORAGE CAPACITY) AIR-COOLED OR WATER-COOLED. ELECTRICAL SPECIFICATIONS: DIRECT WIRE PER CODE (3 WIRES) WATER-COOLED: 115V/60HZ/1PH 13.4 AMPS (20 MAX FUSE) 8388 BTUH. REMOTE: 115V/60HZ/1PH 18.3 AMPS (20 MAX FUSE) 8441 BTUH. (WATER-COOLED) 115V/60HZ/1PH 13.5 AMPS (15 MAX FUSE) 8356 BTUH. PLUMBING SPECIFICATIONS: 3/8\"/>

**ICE-O-MATIC ICE CUBER**



Q-420 CUBER ON S-420 BIN TYPE: AIR-COOLED, WATER-COOLED, REMOTE. ELECTRICAL SPECIFICATIONS: 115/60/1 20 AMP FUSE MIN. AIR-COOLED = 12.3 AMPS, WATER-COOLED = 11.4 AMPS WIRE DIRECT OR PER LOCAL CODE 220-240/50/1 ALSO AVAILABLE. SEE MANUFACTURER. PLUMBING SPECIFICATIONS: 3/8\"/>

**MANITOWOC ICE CUBER**



**ZURN GREASE INTERCEPTOR**

GREASE INTERCEPTOR MANUFACTURER: ZURN INDUSTRIES MODEL: Z1170

SIZE	INLET / OUTLET SIZE	FLOW RATE G.P.M. [L.P.M.]	CAPACITY WATER GAL. [L.]	APPROX. WT. LBS. [KG.]	DIMENSIONS IN INCHES [mm]
100*	4 [102]	3 [76]	8 [191]	42 [19]	10 [254] 7 1/4 [184] 20 3/8 [518] 9 7/8 [251]
200*	7 [178]	5 [127]	14 [325]	53 [24]	11 1/4 [286] 8 1/8 [206] 21 3/4 [552] 11 7/8 [302]
300*	10 [254]	6 [152]	20 [473]	66 [30]	11 3/4 [298] 8 1/4 [210] 25 1/8 [638] 14 [356]
400*	15 [381]	10 [254]	30 [707]	83 [38]	13 3/8 [340] 9 3/8 [238] 27 1/8 [689] 16 3/4 [425]
500	20 [508]	16 [403]	40 [946]	99 [45]	15 [381] 11 3/4 [298] 30 [762] 17 1/4 [438]
600	25 [635]	21 [521]	50 [1170]	124 [56]	17 1/2 [443] 12 1/4 [318] 32 1/4 [819] 19 7/8 [505]
700	35 [889]	30 [762]	70 [1585]	151 [68]	18 3/4 [476] 14 1/4 [362] 34 1/8 [867] 22 1/2 [572]
800	50 [1270]	40 [1016]	100 [2271]	180 [82]	21 1/2 [546] 16 [406]

NOTE: ENGINEERING SPECIFICATIONS: ACID RESISTANT COATED INTERIOR AND EXTERIOR FABRICATED STEEL. INTERNAL AIR RELIEF BYPASS. BRONZE CLEANOUT PLUG. REMOVABLE PRESSURE EQUALIZING/FLOW DIFFUSING INLET BAFFLE. FIXED BOTTOM OUTLET BAFFLE. VISIBLE DOUBLE WALL TRAP SEAL.

**ZURN GREASE INTERCEPTOR**

NOTE: THESE DRAWINGS REPRESENT TYPICAL EQUIPMENT PURCHASED THROUGH DOCTOR'S ASSOCIATES INC. AND DOES NOT REPRESENT ANY EQUIPMENT PURCHASED LOCALLY BY THE FRANCHISEE/OWNER. OWNERS OF STORES OUTSIDE THE UNITED STATES AND CANADA MAY NEED ALTERNATE ELECTRICAL REQUIREMENTS. CONTACT YOUR DAI COORDINATOR FOR THE MODIFIED ELECTRICAL SPECIFICATIONS.

STORE MUST BE CONSTRUCTED AS DESIGNED IN THESE FLOOR PLANS SUBJECT TO FEDERAL, STATE AND LOCAL LAWS. RECIPIENT IS RESPONSIBLE FOR ENSURING COMPLIANCE WITH ALL LAWS. IF MODIFICATIONS ARE NECESSARY, PLEASE CONTACT DAYS STORE DESIGN DEPARTMENT FOR WRITTEN APPROVAL OF THE REQUIRED CHANGES.

THIS DRAWING IS FURNISHED BY DOCTORS ASSOCIATES INC. (DAP) DAPA SUBWAY. RECIPIENT MUST DETERMINE IF THIS DRAWING MUST BE SUBMITTED TO A LICENSED ARCHITECT OR SIMILAR PROFESSIONAL UNDER FEDERAL, STATE OR LOCAL LAW. ANY CHANGES MUST BE APPROVED BY DAI.

DO NOT SCALE DRAWING. WRITTEN DIMENSIONS TAKE PRECEDENCE OVER SCALED DIMENSIONS. AND SHALL BE VERIFIED IN THE FIELD BY THE GENERAL CONTRACTOR AND/OR FRANCHISEE. ANY DISCREPANCIES OR ERRORS AND OMISSIONS IN THE DRAWINGS IF WRITTEN CONFIRMATION HAD NOT BEEN RECEIVED BY DAYS STORE DESIGN DEPARTMENT.

THE GENERAL CONTRACTOR AND EACH SUB-CONTRACTOR SHALL MAKE HIS OWN INSPECTIONS AND MEASUREMENTS. DAI AND SUBWAY SHALL NOT BE HELD RESPONSIBLE FOR THE ACCURACY OF DIMENSIONS AND FOR ERRORS AND OMISSIONS IN THE DRAWINGS IF WRITTEN CONFIRMATION HAD NOT BEEN RECEIVED BY DAYS STORE DESIGN DEPARTMENT.

THIS DRAWING AND THE INFORMATIONAL CONTENT HEREOF IS THE CONFIDENTIAL PROPERTY OF DAI AND IS PROVIDED SOLELY FOR THE USE OF AUTHORIZED FRANCHISEES, THEIR AGENTS AND CONTRACTORS. RECIPIENT AGREES NOT TO REPRODUCE, COPY, USE OR TRANSMIT THIS DRAWING AND ITS INFORMATIONAL CONTENT, IN WHOLE OR IN PART, OR TO ALLOW SUCH ACTION FOR ANY OTHER PERSON, WITHOUT THE WRITTEN PERMISSION OF DAI. EXCEPT WITH THE WRITTEN PERMISSION OF DAI, RECIPIENT SHALL NOT FURTHER DISSEMINATE OR SURRENDER THIS DRAWING AND ANY PERMITTED COPIES HEREON UPON DEMAND.

**SUBWAY**

WORLD HEADQUARTERS

325 BIC DRIVE

MILFORD, CT 06461

(203) 877-4281

(800) 888-4848

REVISION:

DATE	BY	REVISION
6/009	PMR	UPDATED ELECTRICAL SPECS ON REACH-INS

DATE: 10-31-08

DESIGNED BY: PATRICK ROSE

DRAWN BY: PMR REVIEWED BY: PMR

SCALE: NOT TO SCALE

SHEET #:

11820104

PRINTED 4/8/2010